

US005542006A

United States Patent [19]

Shustorovich et al.

[11] Patent Number:

5,542,006

[45] **Date of Patent:**

Jul. 30, 1996

[54] NEURAL NETWORK BASED CHARACTER POSITION DETECTOR FOR USE IN OPTICAL CHARACTER RECOGNITION

- [75] Inventors: Alexander Shustorovich; Christopher W. Thrasher, both of Rochester, N.Y.
- [73] Assignee: **Eastman Kodak Company**, Rochester, N.Y.

1211	Appl No : 263,304	

	[22]	Filed:	Jun.	21,	1994
--	------	--------	------	-----	------

[51]	Int. Cl. ⁶	G06K 9/62
[52]	U.S. Cl	382/156 ; 387/159; 387/173;

[56] References Cited

U.S. PATENT DOCUMENTS

4,933,977 6/1990 Ohnishi et al. 382 5,052,043 9/1991 Gaborski 382/ 5,105,468 4/1992 Guyon et al. 382/ 5,119,438 6/1992 Ueda et al. 382/ 5,131,073 7/1992 Furuta et al. 395/ 5,151,951 9/1992 Ueda et al. 382/ 5,239,593 8/1993 Wittner et al. 382/ 5,245,672 9/1993 Wilson et al. 38. 5,299,269 3/1994 Gaborski et al. 38. 5,440,651 8/1995 Martin 382/1
--

OTHER PUBLICATIONS

A. Shustorovich, "A Subspace Projection Approach to Feature Extraction: The Two-Dimensional Gabor Transform for Character Recognition" to appear in *Neural Networks*, 1994, vol. 7, No. 5.

Y. Bengio et al., "Globally Trained Handwritten Word Recognizer using Spatial Representation, Convolutional Neural Networks. and Hidden Markov Models", Proceedings of 1993 Conference on Neural Information Processing Systems—Natural and Synthetic, Nov. 29–Dec. 2, 1993, Denver, Colorado, pp. 937–944.

A. Gupta et al., "An Integrated Architecture for Recognition of Totally Unconstrained Handwritten Numerals", *International Journal of Pattern Recognition and Artificial Intelligence*, 1993, vol. 7, No. 4, pp. 757–773.

G. Martin et al., "Learning to See Where and What: Training a Net to Make Saccades and Recognize Handwritten Characters" (1993), appears in S. J. Hanson et al. (eds.), Advances in Neural Information Processing Systems, vo 1. 5, pp. 441–447 (Morgan Kaufmann Publishers, San Mateo, CA).

(List continued on next page.)

Primary Examiner—Joseph Mancuso Attorney, Agent, or Firm—Dennis R. Arndt

[57] ABSTRACT

Apparatus, and an accompanying method, for use in an optical character recognition (OCR) system (5) for locating, e.g., center positions ("hearts") of all desired characters within a field (310; 510) of characters such that the desired characters can be subsequently recognized using an appropriate classification process. Specifically, a window (520) is slid in a step-wise convolutional-like fashion (5201, 5202, 520₃) across a field of preprocessed, specifically uniformly scaled, characters. Each pixel in the window is applied as an input to a positioning neural network (152) that has been trained to produce an output activation whenever a character "heart" is spatially coincident with a pixel position within an array (430) centrally located within the window. As the window is successively moved across the field, in a stepped fashion, the activation outputs of the neural network are averaged, on a weighted basis, for each different window position and separately for each horizontal pixel position in the field. The resulting averaged activation output values, typically in the form of a Gaussian distribution for each character, are then filtered, thresholded and then used, via a weighted average calculation with horizontal pixel positions being used as the weights, to determine the character "heart" position as being the center pixel position in the distribution.

23 Claims, 16 Drawing Sheets

